

IN THE CLAIMS

Please amend the claims as follows.

1. (Previously Amended) An apparatus providing equipment and facility redundancy, comprising:
- working circuitry configured to receive and process a first stream of communication data;
- protection circuitry configured to receive and process a second stream of communication data, the second stream being identical to the first stream, the protection circuitry and the working circuitry being functionally identical and synchronized to each other;
- an NxN switch fabric having N input ports and N output ports, wherein each of the N input ports may be connected to any one of the N output ports; and
- a first cross point switch having N input ports and N output ports capable of receiving the processed first stream and the processed second stream, wherein the first cross point switch couples the processed first stream to a first input port of the NxN switch fabric in a first configuration and couples the processed second stream to the first input port in place of the processed first stream in a second configuration upon detection of an error condition in at least one of the working circuitry and the first stream of communication data.
2. (Original) The apparatus of claim 1, wherein the communication data is ATM cells data.

3. (Original) The apparatus of claim 1, wherein the working circuitry receives the first stream from an optical signal and the protection circuitry receives the second stream from the optical signal.

C1 Cont.
4. (Original) The apparatus of claim 1, wherein the working circuitry is implemented on a first circuit board and the protection circuitry is implemented on a second circuit board, the first circuit board being separate and distinct from the second circuit board.

B1 Cont.
5. (Original) The apparatus of claim 1, wherein the working circuitry includes a plurality of first ATM channels performing ATM functions on the first stream and the protection circuitry includes a plurality of second ATM channels performing the ATM functions on the second stream.

6. (Currently Amended) The apparatus of claim 5, wherein one of the first ATM channels and one of the second ATM channels each includes a multiplexer.

7. (Original) The apparatus of claim 5, wherein one of the first ATM channels and one of the second ATM channels includes a SONET framer.

8. (Original) The apparatus of claim 5, wherein one of the first ATM channels and one of the second ATM channels includes a router.

9. (Original) The apparatus of claim 5, wherein one of the first ATM channels and one of the second ATM channels includes a user parameter control unit.

10. (Original) The apparatus of claim 1, further comprising:
a first module including the working circuitry accepts the first stream as input to the working circuitry.

11. (Original) The apparatus of claim 1, further comprising:
a second module including the protection circuitry and having a plurality of ports wherein one of the ports accepts the second stream as input into the protection circuitry.

12. (Previously Cancelled).

13. (Previously Cancelled).

14. (Previously Amended) The apparatus of claim 1, further comprising a second cross point switch having N input ports and N output ports capable of receiving the processed first stream or the processed second stream from a first output port of the NxN switch fabric, wherein the second cross point switch couples the first output port of the NxN switch fabric to at least one of an output portion of a second working circuitry and an output portion of a second protection circuitry.

15. (Original) The apparatus of claim 1, wherein the error condition is a facility error condition.

16. (Original) The apparatus of claim 15, wherein the facility error condition includes a disconnected cable.

17. (Original) The apparatus of claim 1, wherein the error condition is an equipment error condition.

18. (Original) The apparatus of claim 17, wherein the equipment error condition includes at least one of a failure of a SONET Framer a failure of a multiplexer, a failure of a parameter control unit, and a failure of a router.

19. (Previously Amended) A method providing equipment and facility redundancy for ATM circuitry which carries out ATM functions, comprising:

performing a group of ATM functions with first circuitry on a first stream of ATM cells producing a processed first stream;

performing the ATM functions with second circuitry on a second stream of ATM cells producing a processed second stream, the second stream being identical to the first stream, the first circuitry and the second circuitry implementing the ATM functions, the first circuitry and the second circuitry being synchronized to each other; and

in a cross point switch having N input ports capable of receiving the first processed stream and the second processed stream and N output ports coupled to N input ports of an NxN switch fabric, coupling the first processed stream to a first input port of the NxN switch fabric in a first configuration and coupling the second processed stream to the first input port of the NxN switch fabric in place of the first processed stream in a second configuration upon detection of an error condition in the first circuitry, thereby providing redundancy protection for the ATM functions.

20. (Original) The method of claim 19, wherein the ATM functions include at least one of the multiplexing, SONET framing, routing, and user parameter control.

21. (Previously Cancelled).

*Cont.
B1
Cont.*

DOCKET NO. SAMS01-00130
SERIAL NO. 09/276,346
PATENT

22. (Previously Cancelled).
